

Appl. No. 10/734,7653
Amdt. Dated August 10, 2005
Reply to Office Action of May 16, 2005

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) An energy absorbing plunging constant velocity joint comprising:

an outer joint part defining an axis and having a plurality of outer ball tracks[, and] including an outer extended axial range;

an inner joint part defining an axis and having a plurality of inner ball tracks[, and] including an inner extended axial range;

a plurality of torque transmitting balls each guided in a normal axial range of a corresponding pair of said outer and inner ball tracks, wherein each corresponding pair of said inner ball tracks and said outer ball tracks ~~form angles of intersection in~~ are angled with respect of ~~an~~ to their respective part axis, said angles being identical in size but set in opposite directions;

a ball cage having a plurality of cage windows each accommodating one of said balls and which hold said balls in a plane when said torque transmitting balls are in communication with said inner ball tracks and said outer ball tracks; and

one or more energy absorption surfaces distal to the normal axial range and located within the outer extended axial range upon said outer joint part or the inner extended axial range upon said inner joint part, wherein the energy absorption surface interferes with at least one of the plurality of torque transmitting balls when said joint is operated beyond said normal axial range.

2. (withdrawn) The joint according to claim 1, wherein one of the energy absorption surfaces is a circlip.

Appl. No. 10/734,7653
Amdt. Dated August 10, 2005
Reply to Office Action of May 16, 2005

3. (withdrawn) The joint according to claim 2, wherein the circlip is made from a deformable material.

4. (withdrawn) The joint according to claim 3, wherein the deformable material is metal.

5. (withdrawn) The joint according to claim 3, wherein the deformable material is plastic.

6. (withdrawn) The joint according to claim 2, wherein the circlip is a ring.

7. (currently amended) The joint according to claim [[2]] 1, wherein the outer joint part further comprises a cylindrical open end located adjacent the outer extended axial range and distal to the normal axial range of the outer joint part and a grease cover sealingly attached to the cylindrical open end.

8. (original) The joint according to claim 7, wherein the grease cover is displaceable when the joint has axial travel beyond the outer extended axial range.

9. (currently amended) An energy absorbing plunging constant velocity joint comprising:

an outer joint part defining an axis and having a plurality of outer ball tracks[, and] including an outer extended axial range;

an inner joint part defining an axis and having a plurality of inner ball tracks[, and] including an inner extended axial range;

a plurality of torque transmitting balls each guided in a normal axial range of a corresponding pair of said outer and inner ball tracks, wherein each corresponding pair of said inner ball tracks and said outer ball tracks ~~form angles of intersection in~~ are angled with respect to their respective part axis, said angles being identical in size but set in opposite directions;

Appl. No. 10/734,7653
Amdt. Dated August 10, 2005
Reply to Office Action of May 16, 2005

a ball cage having a plurality of cage windows each accommodating one of said balls and which hold said balls in a plane when said torque transmitting balls are in communication with said inner ball tracks and said outer ball tracks; and

one or more energy absorption surfaces distal to the normal axial range and located within the outer extended axial range upon said outer joint part or the inner extended axial range upon said inner joint part, wherein the energy absorption surface interferes with said ball cage or with at least one of the plurality of torque transmitting balls when said joint is operated beyond said normal axial range.

10. (withdrawn) The joint according to claim 9, wherein one of the energy absorption surfaces is a bore surface.

11. (withdrawn) The joint according to claim 10, wherein the bore surface has at least one inclination, stepped inclination or variable inclination.

12. (withdrawn) The joint according to claim 10, wherein the bore surface is made from the same material piece as the outer joint part or the inner joint part.

13. (original) The joint according to claim 9, wherein one of the energy absorption surfaces is a track surface.

14. (original) The joint according to claim 13, wherein the track surface has one or more tapers or a stepped taper.

15. (original) The joint according to claim 14, wherein the track surface is made from the same material piece as the outer joint part or the inner joint part.

16. (original) The joint according to claim 9, wherein the outer joint part further comprises a cylindrical open end located adjacent the outer extended axial

Appl. No. 10/734,7653
Amdt. Dated August 10, 2005
Reply to Office Action of May 16, 2005

range and distal to the normal axial range of the outer joint part and a grease cover sealingly attached to the cylindrical open end.

17. (original) The joint according to claim 16, wherein the grease cover is displaceable when the joint axially travels beyond the outer extended axial range.

18. (withdrawn) The joint according to claim 9 further comprising one or more circlip energy absorption surfaces.

19. (currently amended) A propeller shaft assembly for a vehicle having an energy absorbing plunging constant velocity joint comprising:

an outer joint part defining an axis and having a plurality of outer ball tracks[, and] including an outer extended axial range;

an inner joint part defining an axis and having a plurality of inner ball tracks[, and] including an inner extended axial range;

a plurality of torque transmitting balls each guided in a normal axial range of a corresponding pair of said outer and inner ball tracks, wherein each corresponding pair of said inner ball tracks and said outer ball tracks ~~form angles of intersection in~~ are angled with respect of an to their respective part axis, said angles being identical in size but set in opposite directions;

a ball cage having a plurality of cage windows each accommodating one of said balls and which hold said balls in a plane when said torque transmitting balls are in communication with said inner ball tracks and said outer ball tracks; and

one or more energy absorption surfaces distal to the normal axial range and located within the outer extended axial range upon said outer joint part or the inner extended axial range upon said inner joint part, wherein the energy absorption surface interferes with said ball cage or with at least one of the plurality of torque transmitting balls when said joint is operated beyond said normal axial range;

a hollow shaft connected to said outer joint part; and

a connecting shaft connected to said inner joint part,

Appl. No. 10/734,7653
Amdt. Dated August 10, 2005
Reply to Office Action of May 16, 2005

wherein the hollow shaft is configured to receive the connecting shaft, the inner joint part, the ball cage and the torque transmitting balls when said joint is operated beyond the extended axial range.

20. (original) The joint according to claim 19, wherein the outer joint part further comprises a cylindrical open end located adjacent the outer extended axial range and distal to the normal axial range of the outer joint part and a grease cover sealingly attached to the cylindrical open end, wherein the grease cover is displaceable when the joint axially travels beyond the outer extended axial range.